## UNITED KINGDOM DYNAMIC PLATE TEST DEVICES ACCREDITATION TRIAL SUMMARY TEST CERTIFICATE

Report No: 0171DPT/HeavyDyn Hvy-101A Issue 4

RINCENT HWD HEAVYDYN
SERIAL NUMBER: HVY-101A
TRL Reference No: 50

Operated by **SOCOTEC UK** of **Unit 16 & 17 Oxford Court, Cambridge Road, Granby Industrial Estate, Weymouth** 

has participated in a United Kingdom DPT Accreditation trial on **26 October 2021** at HORIBA-MIRA Proving Ground, Watling Street, Nuneaton, Warwickshire, CV10 OTU under the supervision of TRL.

The above machine has been tested against the accreditation requirements as provided in "Accreditation and Quality Assurance of Dynamic Plate Test Survey Devices" document dated September 2020.

This machine has successfully met the mandatory criteria. Some Network Authorities may also require specific level of performance in some or all of the additional tests. The performance of this machine in each test is summarised in the Annex to this test certificate.

This certificate supersedes any previous certificates issued by TRL.

Signed on behalf of TRL Limited

Patrick Werro

Valid From: 26 October 2021
Date of expiry: 26 November 2022



<sup>&</sup>lt;sup>1</sup> This document is available from TRL or from the UKRLG website (<a href="https://www.ciht.org.uk/ukrlg-home/guidance/road-condition-information/data-collection/dynamic-plate-test-devices-dpt/">https://www.ciht.org.uk/ukrlg-home/guidance/road-condition-information/data-collection/dynamic-plate-test-devices-dpt/</a>).

## Test Report 0171DPT/HeavyDyn Hvy-101A Issue 4 Annex

The following parameters cover the configuration of the DPT device.

Component	Parameter
Load plate type	Solid
Number of weights / buffers per side	10/4
Peak smoothing feature	N/A

The following parameters must be passed to successfully meet the requirements of the trial.

Tested Parameter	Performance
Standard deviation of load corrected deflections	Pass
Mean Field Calibration Factor (FCF) for all sensors	Pass
Field Calibration Factor (FCF) for individual sensors	Pass
Mean Standard Deviation of the Deviation Ratio (SDDR) for all sensors	Pass
SDDR for individual sensors	Pass
Distance Travelled	Pass

## **Comments:**

The following parameters were also tested/reviewed. They are not currently mandatory requirements, however some Network Authorities may also require specific level of performance in some or all of these additional tests.

Tested Parameter	Performance level
OSGR coordinates (Easting and Northing)	Medium
Temperature at Depth	High
Surface temperature	Low
Air temperature	Medium

## Comments:

3-dimensional location referencing data supplied as latitude and longitude. For this assessment the Auditor has completed the transformation to OSGRs. As such the contractor's coordinate transformation to OSGR has not been assessed.

